

mitsubishi triton single cab 2wd

GRADE	KA4TNENMFRU 2.5 SINGLE CAB GL
DIMENSION & WEIGHT	
OVER LENGTH (mm)	5030
OVERALL WIDTH (mm)	1750
OVERALL HIGHT (mm)	1655
WHEELBASE (mm)	3000
FRONT TRACK (mm)	1505
REAR TRACK (mm)	1500
BED INTERIOR LENGTH (mm)	2220
BED INTERIOR WIDTH (mm)	1470
BED INTERIOR HEIGHT (mm)	405
GROUND CLEARANGE (mm)	200
CURB WEIGHT APPROX. (Kg)	1505
PERFORMANCE	
MINIMUM TURNING RADIUS	5.7
MAXIMUM CLIMBING ABILITY	0.31
MODEL	4D56 DEISEL TURBO
TYPY	4-CYLINDER SOHC
DISPLACEMENT (CC)	2477
BORE x STROKE (MM)	91.1 x 95.0
COMPRESSION RATIO	21.0 : 1
MAXIMUM OUTPUT - ECE NET (Kw/PS / RPM)	66 (90) /4000
MAXIMUM TORGUE (N-m / Kg-m / RPM)	196 / 2000
FUEL SYSTEM	
TYPE	ELETRONIC FUEL INJECTION
FUEL TANK CAPACITY (LITRE)	75
TRANSMISSION	
CLUTCH	MECHANICAL
TYPE	MANUAL 5 SPEED
GEAR RATIO GEAR1	3.967
GEAR2	2.136
GEAR3	1.360
GEAR4	1.000
GEAR5	0.856
REVERSE GEAR	3.578
FINAL GEAR RATIO	4.222
STEERING	
TYPE	RACK AND PINION WITH POWER STEERING
SUSPENSION	
FRONT	INDEPENDENT-WISHBONE,COIL SPRING
REAR	REGID-ELLIPTIC LEAF SPRING
BRAKE	
FRONT	VENTILATED DISCS
REAR	LEADING AND TRAILING DRUMS
TIRE SIZE	195R15C

TRITON SINGLE CAB 4WD STANDARD EQUIPMENTS

EXTERIOR	
GREEN GLASS	
INTERMITTENT WINDSHIELD WIPER	
REAR TAIL GATE OPENER	
REFLECTOR	
INTERIOR	
POWER STEERING	
DAY-NIGHT REAR VIEW MIRROR	
CLOCK	
SUN VISOR	

BUILT IN DOWN LIGHT AT CENTRAL PANEL	
TACHOMETER	
DIGITAL DUAL TRIP METER	
RADIO-CASSETTE TAPE	
CIGAR LIGHTER WITH ASHTRAY	
TILT VINYL	
STORAGE BOX WITH LAMP	
CONVENIENCE HOOK FOR DRIVER SIDE	
FOOT REST	
SAFETY	
LAMINATED FRONT WINDSHIELD	
FRONT SEAT BELT 3 POINT ELR , 2 POINT	
SIDE DOOR IMPACT BAR	
LSPV	
EURO STEP III	