



Model	Comfort	Luxury
Engine		
Model	QR 25 DE	QR 25 DE
Type	4 cylinder-inline DOHC 16 valves with Continuously Variable Valve Timing Control (CVTC)	4 cylinder-inline DOHC 16 valves with Continuously Variable Valve Timing Control (CVTC)
Fuel System	Electronic Multi-Point fuel injection controlled by ECCS	Electronic Multi-Point fuel injection controlled by ECCS
Bore x Stroke (mm.)	89 x 100	89 x 100
Displacement (cc.)	2,488	2,488
Compression ratio	9.5: 1	9.5: 1
Max.Power (EEC-NET) Kw(PS)/rpm	132 (180) / 6,000	132 (180) / 6,000
Max.Torque Nm(Kg-m)/rpm	245 (25) / 4,000	245 (25) / 4,000
Fuel tank capacity litre	60	60
Transmission		
Transmission System	4-speed automatic transmission	4-speed automatic transmission
Gear ratio		
1st	2.785	2.785
2nd	1.545	1.545
3rd	1.000	1.000
4th	0.684	0.684
Reverse	2.272	2.272
Transfer Gear Ratio	0.404	0.404
Final gear	4.087	4.087
Wheel and tire		
Alloy wheels	6.5 JJ - 16	6.5 JJ - 16
Tires	215/65R16	215/65R16