

ISUZU D-MAX RODEO

GRADE	ROREO	RODEO
ENGINE		
MODEL	4JJ1-TCX	4JK1-TC
TYPE	4-CYLINDER , DOHC 16-VALVE DIRECT INJECTION COMMON RAIL (D-4D) TURBO (VGS) ,INTER COOLER	4-CYLINDER , DOHC 16-VALVE DIRECT INJECTION COMMON RAIL (D-4D) TURBO ,INTER COOLER
DISPLACEMENT (cc)	2999	2499
BORE x STROKE (mm)	95.4 x 104.9	95.4 x 87.4
COMPRESSION RATIO	17.5	18.3
MAXIMUM OUTPUT (Kw(Hp) / RPM)	120 / 3600	85 / 3600
MAXIMUM TORQUE (N-M / RPM)	360 / 1800-2800	280 / 1800-2200
TRANSMISSION		
CLUTCH	MECHANICAL	
TRANSMISSION TYPE	5 SPEED MANUAL	
TRANSMISSION GEAR RATIO GEAR1 / 2 / 3 / 4 / 5	4.326 / 2.557 / 1.490 / 1.000 / 0.790	4.008 / 2.301 / 1.427 / 1.000 / 0.745
REVERSE GEAR	3.942	3.651
TRANSFER	2482 / 1000	
DIFFERENTIAL GEAR RATION	3.727 / (41/11)	3.909/ (43/11)
STEERING SYSTEM		
TYPE	RACK AND PINION , POWER ASIST	
RATIO	47.0	
MINIMUM TURNING RADIUS	6.1	
BRAKE SYSTEM		
FRONT	VENTILATED DISC	
REAR	LEADING-TRAILING DRUM	
SUSPENSION		
FRONT	DOUBLE WISHBONE WITH TORSION BAR,GAS-CHARGED SHOCK ABSORBER AND STABILIZER	
REAR	LEAF SPRING , RIGID AXEL WITH GAS-CHARGED SHOCK ABSORBER	
OVERALL LENGHT (mm)	5040	
OVERALL WIDTH (mm)	1800	
OVERALL HEIGHT (mm)	1755	
WHEEL BASE	3050	
THREAD FRONT	1520	
THREAD REAR	1525	
GROUND CLEARANCE	225	
CURB WEIGHT APPROX. (Kg)	1595	1585
WHEEL & TIRES	7.0JJ x 16 , 245/70 R16	
FUEL CAPACITY (LITRE)	76	

Subject to change without prior notice.