

ISUZU D-MAX SPACECAB

GRADE	SPACECAB		
	SLX	SX	SLX/SLX SMART
MODEL	4JJ1-TC	4JK1-TC	
TYPE	4-CYLINDER , DOHC 16-VALVE DIRECT INJECTION COMMON RAIL (D-4D) TURBO ,INTER COOLER		
DISPLACEMENT (cc)	2999	2499	
BORE x STROKE (mm)	95.4 x 104.9	95.4 x 87.4	
COMPRESSION RATIO	17.5	18.3	
MAXIMUM OUTPUT (Kw(Hp) / RPM)	107 / 3600	85 / 3600	
MAXIMUM TORQUE (N-M / RPM)	294 / 1400-3400	280 / 1800-2200	
TRANSMISSION			
CLUTCH MT	MECHANICAL		
AT	TORUGE CONVERTER		
TRANSMISSION TYPE MT	5 SPEED MANUAL		
AT	4 SPEED		
TRANSMISSION GEAR RATIO GEAR1 / 2 / 3 / 4 / 5	2.785/ 1.545 / 1.000 / 0.694	4.008 / 2.301 / 1.427 / 1.000 / 0.745	
REVERSE GEAR	2.272	3.651	
TRANSFER	2482 / 1000		
DIFFERENTIAL GEAR RATION	3.727 / (41/11)	3.909/ (43/11)	
STEERING SYSTEM			
TYPE	RACK AND PINION , POWER ASIST		
RATIO	40.80		
MINIMUM TURNING RADIUS	5.9		
BRAKE SYSTEM			
FRONT	VENTILATED DISC		
REAR	LEADING-TRAILING DRUM		
SUSPENSION			
FRONT	DOUBLE WISHBONE WITH TORSION BAR,GAS-CHARGED SHOCK ABSORBER AND STABILIZER		
REAR	LEAF SPRING , RIGID AXEL WITH GAS-CHARGED SHOCK ABSORBER		
OVERALL LENGHT (mm)	5045		
OVERALL WIDTH (mm)	1720		
OVERALL HEIGHT (mm)	1640		
WHEEL BASE	3050		
THREAD FRONT	1460		
THREAD REAR	1460		
GROUND CLEARANCE	195		
CURB WEIGHT APPROX. (Kg)	1545	1515	1530
WHEEL & TIRES	6.5.0JJ x 15 , 215/70 R15		
FUEL CAPACITY (LITRE)	76		

Subject to change without prior notice.