

## ISUZU D-MAX CAB4

GRADE	CAB 4 LS		CAB 4 SLX
	A/T	M/T	M/T
<b>ENGINE</b>			
MODEL	4JJ1-TCX		
TYPE	4-CYLINDER , DOHC 16-VALVE DIRECT INJECTION COMMON RAIL (D-4D) TURBO (VGS),INTER COOLER		4-CYLINDER , DOHC 16-VALVE DIRECT I
DISPLACEMENT (cc)	2999		
BORE x STROKE (mm)	95.4 x 104.9		
COMPRESSION RATIO	17.5		
MAXIMUM OUTPUT (Kw(Hp) / RPM)	120 / 3600		
MAXIMUM TORQUE (N-M / RPM)	333/ 1600-3200	360/ 1800-2800	
<b>TRANSMISSION</b>			
CLUTCH M/T		MECHANICAL	
CLUTCH A/T	TORQUE CONVERTER		
<b>TRANSMISSION TYPE</b>			
TRANSMISSION GEAR RATIO GEAR1	2.804	4.326	
GEAR2	1.532	2.557	
GEAR3	1.000	1.490	
GEAR4	0.705	1.000	
GEAR5		0.790	
REVERSE GEAR	2.394	3.942	
	2.482/1.000		
TRANSFER			
DIFFERENTIAL GEAR RATION	4.100 (41/10)	3.727 (41/11)	
<b>STEERING SYSTEM</b>			
TYPE	RACK AND PINION , POWER ASIST		
RATIO	47.00		
MINIMUM TURNING RADIUS	6.1		
<b>BRAKE SYSTEM</b>			
FRONT	VENTILATED DISC		
REAR	LEADING-TRAILING DRUM		
<b>SUSPENSION</b>			
FRONT	DOUBLE WISHBONE WITH TORSION BAR, GAS-CHARGED SHOCK ABSORBER AND STABILIZER		DOUBLE WIS GAS-CHARGED SI
REAR	LEAF SPRING , RIGID AXEL WITH GAS-CHARGED SHOCK ABSORB		
<b>DEMENSION - EXTIOR</b>			
OVERALL LENGHT (mm)	4925		
OVERALL WIDTH (mm)	1800		
OVERALL HEIGHT (mm)	1760		
WHEEL BASE	3050		
THREAD FRONT	1510		
THREAD REAR	1525		
GROUND CLEARANCE	225		
CURB WEIGHT APPROX. (Kg)	1745	1730	1580
FUEL CAPACITY (LITRE)	76		

